**TECHNICAL DATA** 

## ROSA ROUND LED PANEL

# TOPE & LIGHTING\_

# PRODUCT DATASHEET ROSA80\_R\_8W\_LED\_580

A recessed LED luminaire with a 10mm no frame profile. Electronic, fixed output gear. IP65 environmental degree, IK08.

Driver IP20, IK03. Body: aluminum white painted (RAL9016). Diffuser: Polycarbonate, UV-stabilised. Electrical connection via push wire terminal blocks. Complete with 4000K LED.

IP65 IK08	78,73 lm/W
-----------	------------



SKU:

6003000043

	3.0. 0003000013
Electrical data	
Nominal wattage	8 W
Operating wattage	7,379 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz
Photometrical data	
Color temperature (CCT)	4000 K
Luminous efficiency	78,73 lm/W
Luminous flux	581 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5
Light technical data	
Beam angle	1200
Dimensions and weight	
Diameter	Ø100 mm
Height	24 mm
Weight Neto	0,152 kg
Cut out hole size	Ø75mm
Materials	
Body material	Aluminum
Housing color	White
Difuser material	Polycarbonate, UV-stabilised.
Operating conditions	
Ambient temperature range	-20+65°C
Lifespan	
Lifespan L80/B10 at 25°	50000 h
Led Brand	EPISTAR
Driver	LS-8-250SI1-ZD

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

### Mounting information

Mounting type	Recessed
Mounting location	Ceiling
Capabilities	
Dimmable	No
Type of connection	Wires 2-pole
Standards and Certificates	
Protection class IK	IK08
Type of protection IP	IP65
Standards	CE, RoHS
Warranty	36 months


#### **LOGISTICAL DATA**

Main package

Product code	6003000043	
Package	Carton	
Units in carton	1 pcs	
Package diameters, weight bruto	175x145x30 mm, 0,198 kg	
Product EAN code	4772007007424	
Second package		
Package	Carton box	
Units in second package	100 pcs	
Package diameters, weight bruto	820x375x310 mm; 20,814 kg	
ShipPing carton EAN code	4772007007523	

#### **ACCESSORIES**

### **ENERGY EFFICIENCY**



#### **ALL FAMILY PRODUCTS**

6003000042 ROSA80\_R\_6W\_LED\_400 6003000043 ROSA80\_R\_8W\_LED\_580 6003000044 ROSA80\_R\_10W\_LED\_800 6003000045 ROSA80\_R\_14W\_LED\_1110 6003000046 ROSA80\_R\_20W\_LED\_1740 6003000047 ROSA80\_R\_28W\_LED\_2270

