OSLO LED DOWNLIGHT

TOPE & LIGHTING_

PRODUCT DATASHEET OSLO100_W_15W_LED_1500

Surface LED spotlight with flood distribution. 360° rotatable. 90° tilt adjustable.

IP20. Body: Aluminium powder coated white color. Complete with 4000K LED

IP20 IK05 3	107,79 lm/W
-------------	-------------



TECHNICAL DATA		SKU:	6005000029
Electrical data			
Nominal wattage	15 W		
Operating wattage	13,72 W		
Nominal Voltage	165-240 V		
Power factor	≥0.50		
Mains frequency	50/60 Hz		
Photometrical data			
Color temperature (CCT)	4000 K		
Luminous efficiency	107,79 lm/W		
Luminous flux	1479 lm		
Color rendering index (CRI)	≥80		
Unified Glare Rating (UGR)	<21,5		
Light technical data			
Beam angle	24°		
Dimensions and weight			
Diameter	Ø100 mm		
Height	105 mm		
Weight Neto	0,438 kg		
Materials			
Body material	Aluminium		
Housing color	White		
Difuser material	Polycarbonate, UV-sta	ibilised.	
Operating conditions			
Ambient temperature range	-20+65°C		
Lifespan			
Lifespan L80/B10 at 25°	50000 h		
Led Brand	EPISTAR		
Driver	DL-12W300-L		

Mounting information

1110 0011111111111111111111111111111111	
Mounting type	Surfaced
Mounting location	Ceiling/ Wall
Capabilities	
Dimmable	No
Type of connection	Wires 2-pole
Standards and Certificates	
Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package

Product code	6005000029
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	110x110x120 mm; 0,486 kg
Product EAN code	4772007006137
Second package	
Package	Carton box
Units in second package	24 pcs
Package diameters, weight bruto	450x240x380 mm; 12,226 kg
ShipPing carton EAN code	4772007006922

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6005000030 OSLO100_B_10W_LED_1000 6005000031 OSLO100_B_15W_LED_1500 6005000028 OSLO100_W_10W_LED_1000 6005000029 OSLO100_W_15W_LED_1500

