**TECHNICAL DATA** 

#### **SPLIT ROUND LED PANEL**

# PRODUCT DATASHEET SPLIT80\_R\_16W\_LED\_1280

A recessed LED luminaire with 7mm profile. Electronic, fixed output gear. IP44 protection degree. IK05. Body: sheet aluminum white (RAL9016). Diffuser: Polycarbonate, UV-stabilised. Electrical connection via push wire terminal blocks. Complete with 4000K LED. With integrated driver.

IP44	IK05	76,48 lm/W
------	------	------------



SKU:

6003000020

TECHNICAL DATA		JKU.	0003000020
Electrical data			
Nominal wattage	16 W		
Operating wattage	15,27 W		
Nominal Voltage	165-240 V		
Power factor	≥0.50		
Mains frequency	50/60 Hz		
Photometrical data			
Color temperature (CCT)	4000 K		
Luminous efficacy	76,48 lm/W		
Luminous flux	1168 lm		
Color rendering index (CRI)	≥80		
Unified Glare Rating (UGR)	<21.5		
Light technical data			
Beam angle	120°		
Dimensions and weight			
Diameter	Ø150 mm		
Height	30 mm		
Weight Neto	0,268 kg		
Cut out hole size	Ø130mm		
Materials			
Body material	Aluminum		
Housing color	White		
Difuser material	Polycarbonate, UV-stabilised.		
Operating conditions			
Ambient temperature range	-20+65°C		
Lifespan			
Lifespan L80/B10 at 25°	50000 h		
Led Brand	EPISTAR		
Driver	TOPE (YLQD-6-16)		
Mounting information			
Mounting type	Recessed	Recessed	
Mounting location	Ceiling		

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

### Capabilities

Dimmable	No
Type of connection	Wires 2-pole
Standards and Certificates	
Protection class IK	IK05
Type of protection IP	IP44
Standards	CE, RoHS
Warranty	36 months

### LOGISTICAL DATA

Main package

Product code	6003000020	
Package	Carton	
Units in carton	1 pcs	
Package diameters, weight bruto	160x153x32mm; 0,310 kg	
Product EAN code	4772007005086	
Second package		
Package	Carton box	
Folding carton boxes in shiPping carton	60 pcs	
Package diameters, weight bruto	500x365x335mm ; 19,182 kg	
ShipPing carton EAN code	4772007005628	

#### **ACCESSORIES**

## **ENERGY EFFICIENCY**



6003000017

6003000018

### **ALL FAMILY PRODUCTS**

6003000020	SPLIT80_R_16W_LED_1140
6003000021	SPLIT80_R_22W_LED_1570
6003000022	SPLIT80_R_30W_LED_2150
6003000023	SPLIT80_S_5W_LED_355
6003000024	SPLIT80_S_8W_LED_570
6003000026	SPLIT80_S_16W_LED_1140
6003000027	SPLIT80_S_22W_LED_1570
6003000028	SPLIT80 S 30W LED 2150

SPLIT80\_R\_5W\_LED\_355

SPLIT80\_R\_8W\_LED\_570

