SPLITROUND LED PANELPRODUCT DATASHEETSPLIT80_R_30W_LED_2150

A recessed LED luminaire with 7mm profile. Electronic, fixed output gear. IP44 protection degree. IK05. Body: sheet aluminum white (RAL9016). Diffuser: Polycarbonate, UV-stabilised. Electrical connection via push wire terminal blocks. Complete with 4000K LED. With integrated driver.



IP44 IK05 81,44 lm/W

TECHNICAL DATA		SKU:	6003000022
Electrical data			
Nominal wattage	30 W		
Operating wattage	26,36 W		
Nominal Voltage	165-240 V		
Power factor	≥0.50		
Mains frequency	50/60 Hz		
Photometrical data			
Color temperature (CCT)	4000 K		
Luminous efficacy	81,44 lm/W		
Luminous flux	2147 lm		
Color rendering index (CRI)	≥80		
Unified Glare Rating (UGR)	<21.5		
Light technical data			
Beam angle	120°		
Dimensions and weight			
Diameter	Ø225 mm		
Height	30 mm		
Weight Neto	0,516 kg		
Cut out hole size	Ø195mm		
Materials			
Body material	Aluminum		
Housing color	White		
Difuser material	Polycarbonate, UV-stab	Polycarbonate, UV-stabilised.	
Operating conditions			
Ambient temperature range	-20+65°C		
Lifespan			
Lifespan L80/B10 at 25°	50000 h		
Led Brand	EPISTAR		
Driver	TOPE (YLQD-6-30)		
Mounting information			
Mounting type	Recessed		
Mounting location	Ceiling		

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications

			announcement.	

© TopE Lighting



Capabilities


Dimmable	No		
Type of connection	Wires 2-pole		
Standards and Certificates			
Protection class IK	IK05		
Type of protection IP	IP44		
Standards	CE, RoHS		
Warranty	36 months		

LOGISTICAL DATA

6003000022
Carton
1 pcs
235x230x30 mm ; 0,598 kg
4772007005109
Carton box
20 pcs
480x370x255 mm ; 12,470 kg
4772007005642

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6003000017	SPLIT80_R_5W_LED_355
6003000018	SPLIT80_R_8W_LED_570
6003000020	SPLIT80_R_16W_LED_1140
6003000021	SPLIT80_R_22W_LED_1570
6003000022	SPLIT80_R_30W_LED_2150
6003000023	SPLIT80_S_5W_LED_355
6003000023 6003000024	SPLIT80_S_5W_LED_355 SPLIT80_S_8W_LED_570
6003000024	SPLIT80_S_8W_LED_570
6003000024 6003000026	SPLIT80_S_8W_LED_570 SPLIT80_S_16W_LED_1140



TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications

without	prior	notification	or public	announcement.