

## PRODUCT DATASHEET

### TANGA90\_12W\_B\_3K\_LED\_1080

LED spotlight with flood distribution.

Fixed output control gear.

Surface mounted. IP20 environmental degree.

Body: die- cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

96,60 lm/W

#### TECHNICAL DATA

Product code

6006000035

##### Electrical data

Nominal wattage	12 W
Operating wattage	11,18 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

##### Photometrical data

Color temperature (CCT)	3000 K
Luminous efficiency	96,60 lm/W
Luminous flux	1080 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

##### Light technical data

Beam angle	45°
------------	-----

##### Dimensions and weight

Dimensions	75x75x140 mm
Weight Neto	0,430 kg

##### Materials

Body material	Aluminium
Housing color	Black
Difuser material	Polycarbonate, UV-stabilised.

##### Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

##### Lifespan

Lifespan L80/B10 at 25°	30000 h
Led Brand	BRIDGELUX
Driver	DL-12W300-L

##### Mounting information

Mounting type	Surfaced
Mounting location	Ceiling

##### Capabilities

Dimmable	No
Type of connection	Wires 2-pole

## Standards and Certificates

Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

## LOGISTICAL DATA

### Main package


Product code	6006000035
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	159x80x80 mm ; 0,468 kg
Product EAN code	4772007012770

### Second package

Package	Carton
Units in second package	50 pcs
Package diameters, weight bruto	430x430x335 mm ; 23,952 kg
ShipPing carton EAN code	4772007013685

## ACCESSORIES

## ENERGY EFFICIENCY



## ALL FAMILY PRODUCTS

6006000031	TANGA90_7W_W_3K_LED_630
6006000032	TANGA90_12W_W_3K_LED_1080
6006000033	TANGA90_15W_W_3K_LED_1350
6006000034	TANGA90_7W_B_3K_LED_630
6006000035	TANGA90_12W_B_3K_LED_1080
6006000036	TANGA90_15W_B_3K_LED_1350