

PRODUCT DATASHEET

TANGA90_15W_W_3K_LED_1350

LED spotlight with flood distribution.

Fixed output control gear.

Surface mounted. IP20 environmental degree.

Body: die- cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

94,60 lm/W

TECHNICAL DATA

Product code

6006000033

Electrical data

Nominal wattage	15 W
Operating wattage	14,27 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

Photometrical data

Color temperature (CCT)	3000 K
Luminous efficiency	94,60 lm/W
Luminous flux	1350 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

Light technical data

Beam angle	45°
------------	-----

Dimensions and weight

Dimensions	96x96x150 mm
Weight Neto	0,648 kg

Materials

Body material	Aluminium
Housing color	White
Difuser material	Polycarbonate, UV-stabilised.

Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

Lifespan

Lifespan L80/B10 at 25°	30000 h
Led Brand	BRIDGELUX
Driver	DL-20W-300-L

Mounting information

Mounting type	Surfaced
Mounting location	Ceiling

Capabilities

Dimmable	No
Type of connection	Wires 2-pole

Standards and Certificates

Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

LOGISTICAL DATA

Main package


Product code	6006000033
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	160x105x105 mm ; 0,698 kg
Product EAN code	4772007012756

Second package

Package	Carton
Units in second package	30 pcs
Package diameters, weight bruto	560x335x335 mm ; 21,786 kg
ShipPing carton EAN code	4772007013661

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

6006000031	TANGA90_7W_W_3K_LED_630
6006000032	TANGA90_12W_W_3K_LED_1080
6006000033	TANGA90_15W_W_3K_LED_1350
6006000034	TANGA90_7W_B_3K_LED_630
6006000035	TANGA90_12W_B_3K_LED_1080
6006000036	TANGA90_15W_B_3K_LED_1350