

## PRODUCT DATASHEET

### TARTU80\_10W\_W\_4\_LED\_900

LED spotlight with flood distribution.

Fixed output control gear.

Suspended mounting, (max 90cm long wire ).

IP20 enviromental degree.

Body: die- cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

91,49 lm/W

TECHNICAL DATA		Product code	6006000037
Electrical data			
Nominal wattage	10 W		
Operating wattage	9,837 W		
Nominal Voltage	165-240 V		
Power factor	≥0.50		
Mains frequency	50/60 Hz		
Photometrical data			
Color temperature (CCT)	3000 K		
Luminous efficiency	91,49 lm/W		
Luminous flux	900 lm		
Color rendering index (CRI)	≥80		
Unified Glare Rating (UGR)	<21,5		
Light technical data			
Beam angle	36°		
Dimensions and weight			
Diameter	Ø60 mm		
Height	395 mm		
Weight Neto	0,576 kg		
Materials			
Body material	Aluminium		
Housing color	White		
Difuser material	Polycarbonate, UV-stabilised.		
Operating conditions			
Ambient temperature range	-20...+65°C		
Lifespan			
Lifespan L80/B10 at 25°	30000 h		
Led Brand	BRIDGELUX		
Driver	8-12W		
Mounting information			
Mounting type	Suspended		
Mounting location	Ceiling		
Capabilities			
Dimmable	No		
Type of connection	Wires 2-pole		

## Standards and Certificates

Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

## LOGISTICAL DATA

### Main package


Product code	6006000037
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	520x67x67 mm ; 0,644 kg
Product EAN code	4772007012886

### Second package

Package	Carton
Units in second package	25 pcs
Package diameters, weight bruto	535x355x345 mm ; 16,908 kg
ShipPing carton EAN code	4772007013708

## ACCESSORIES

## ENERGY EFFICIENCY



## ALL FAMILY PRODUCTS

6006000037	TARTU80_10W_W_4_LED_900
6006000038	TARTU80_10W_W_5_LED_900
6006000039	TARTU80_10W_W_6_LED_900
6006000040	TARTU80_10W_W_7_LED_900
6006000041	TARTU80_10W_B_4_LED_900
6006000042	TARTU80_10W_B_5_LED_900
6006000043	TARTU80_10W_B_6_LED_900
6006000044	TARTU80_10W_B_7_LED_900