

## PRODUCT DATASHEET

### TULSA90\_10W\_W\_3K\_LED\_900

LED spotlight with flood distribution.

Fixed output control gear.

Surface mounted. IP20 environmental degree.

Body: die- cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

96,51 lm/W

#### TECHNICAL DATA

SKU:

6006000025

##### Electrical data

Nominal wattage	10 W
Operating wattage	9,325 W
Nominal Voltage	165-240 V
Power factor	≥0.50
Mains frequency	50/60 Hz

##### Photometrical data

Color temperature (CCT)	3000 K
Luminous efficiency	96,51 lm/W
Luminous flux	900 lm
Color rendering index (CRI)	≥80
Unified Glare Rating (UGR)	<21,5

##### Light technical data

Beam angle	45°
------------	-----

##### Dimensions and weight

Diameter	Ø53 mm
Height	100 mm
Weight Neto	0,168 kg

##### Materials

Body material	Aluminium
Housing color	White
Difuser material	Polycarbonate, UV-stabilised.

##### Operating conditions

Ambient temperature range	-20...+65°C
---------------------------	-------------

##### Lifespan

Lifespan L80/B10 at 25°	30000 h
Led Brand	BRIDGELUX
Driver	DL-12W-L-01

##### Mounting information

Mounting type	Surfaced
Mounting location	Ceiling

##### Capabilities

Dimmable	No
Type of connection	Wires 2-pole

## Standards and Certificates

Protection class IK	IK05
Type of protection IP	IP20
Standards	CE, RoHS
Warranty	36 months

## LOGISTICAL DATA

### Main package


Product code	6006000025
Package	Carton
Units in carton	1 pcs
Package diameters, weight bruto	120x70x65 mm ; 0,192 kg
Product EAN code	4772007012664

### Second package

Package	Carton
Units in second package	100 pcs
Package diameters, weight bruto	680x350x265 mm ; 19,924 kg
ShipPing carton EAN code	4772007013586

## ACCESSORIES

## ENERGY EFFICIENCY



## ALL FAMILY PRODUCTS

6006000025	TULSA90_10W_W_3K_LED_900
6006000026	TULSA90_15W_W_3K_LED_1350
6006000027	TULSA90_20W_W_3K_LED_1800
6006000028	TULSA90_10W_B_3K_LED_900
6006000029	TULSA90_15W_B_3K_LED_1350
6006000030	TULSA90_20W_B_3K_LED_1800