

PRODUCT DATASHEET

TULSA90_15W_B_3K_LED_1350

LED spotlight with flood distribution.

Fixed output control gear.

Surface mounted. IP20 environmental degree.

Body: die-cast aluminium, painted white or black.

Complete with 3000K LED



IP20

IK05

96,49 lm/W

TECHNICAL DATA

SKU:

6006000029

Electrical data

| | |
|-------------------|-----------|
| Nominal wattage | 15 W |
| Operating wattage | 13,99 W |
| Nominal Voltage | 165-240 V |
| Power factor | ≥0.50 |
| Mains frequency | 50/60 Hz |

Photometrical data

| | |
|-----------------------------|------------|
| Color temperature (CCT) | 3000 K |
| Luminous efficiency | 96,49 lm/W |
| Luminous flux | 1350 lm |
| Color rendering index (CRI) | ≥80 |
| Unified Glare Rating (UGR) | <21,5 |

Light technical data

| | |
|------------|-----|
| Beam angle | 45° |
|------------|-----|

Dimensions and weight

| | |
|-------------|----------|
| Diameter | Ø95 mm |
| Height | 140 mm |
| Weight Neto | 0,474 kg |

Materials

| | |
|------------------|-------------------------------|
| Body material | Aluminium |
| Housing color | Black |
| Difuser material | Polycarbonate, UV-stabilised. |

Operating conditions

| | |
|---------------------------|-------------|
| Ambient temperature range | -20...+65°C |
|---------------------------|-------------|

Lifespan

| | |
|-------------------------|-------------|
| Lifespan L80/B10 at 25° | 30000 h |
| Led Brand | BRIDGELUX |
| Driver | DL-20W-L-01 |

Mounting information

| | |
|-------------------|----------|
| Mounting type | Surfaced |
| Mounting location | Ceiling |

Capabilities

| | |
|--------------------|--------------|
| Dimmable | No |
| Type of connection | Wires 2-pole |

Standards and Certificates

| | |
|-----------------------|-----------|
| Protection class IK | IK05 |
| Type of protection IP | IP20 |
| Standards | CE, RoHS |
| Warranty | 36 months |

LOGISTICAL DATA

Main package


| | |
|---------------------------------|---------------------------|
| Product code | 6006000029 |
| Package | Carton |
| Units in carton | 1 pcs |
| Package diameters, weight bruto | 150x100x100 mm ; 0,518 kg |
| Product EAN code | 4772007012701 |

Second package

| | |
|---------------------------------|----------------------------|
| Package | Carton |
| Units in second package | 30 pcs |
| Package diameters, weight bruto | 520x325x320 mm ; 16,216 kg |
| ShipPing carton EAN code | 4772007013623 |

ACCESSORIES

ENERGY EFFICIENCY



ALL FAMILY PRODUCTS

| | |
|------------|---------------------------|
| 6006000025 | TULSA90_10W_W_3K_LED_900 |
| 6006000026 | TULSA90_15W_W_3K_LED_1350 |
| 6006000027 | TULSA90_20W_W_3K_LED_1800 |
| 6006000028 | TULSA90_10W_B_3K_LED_900 |
| 6006000029 | TULSA90_15W_B_3K_LED_1350 |
| 6006000030 | TULSA90_20W_B_3K_LED_1800 |