


HQS-9.6W-60LED-WW2K7W-24V

Professional Led Strip, 9.6 W/m



TECHNICAL DETAILS

SUPPLY VOLTAGE	24 V ± 0.5 VDC
POWER	9.6 W/m
CURRENT	0.4 A/m
POWER PER REEL (5M)	48 W
COLOR TEMPERATURE	2700K / 3000-6500K
BEAM ANGLE	120°
LUMINOUS FLUX PER METER	460 lm
CRI	80
MAXIMUM LENGTH FOR ONE SIDED SUPPLY	5 m
IP PROTECTION DEGREE	IP33
WORKING TEMPERATURE	-25°C ~ 50°C
STORAGE TEMPERATURE	-25°C ~ 60°C
LED QTY (PER METER)	60 LEDs/m
WIDTH PCB	10 mm
CUT SECTION	100 mm
CONNECTION WIRE	2 x AWG20 (0.52 mm ²) stranded wire, length = 140 mm: V+: red: V:-black
DIMENSIONS (L * W * H)	5000 x 10 x 1.7 mm
PACKING	5 m /roll (bag); 60 pcs / ctn; ctn dimensions: 45 x 25 x 25.6 cm

ENERGY
MW LIGHTING
 HQS-9.6W-60LED-WW2K7W-24V

A
B
C
D
E
F
G

3 kWh/1000h

2019/2015

